

Please replace The Brief Description of the Drawings sections with the following rewritten section:

--The invention will be better understood by reference to the accompanying drawings, wherein:

FIGURE 1 is a perspective view of a typical line trimmer and guard embodiment of this invention;

FIGURE 2 is a perspective view of a typical line trimmer motor and shaft, fitted with a coupling flange for mounting the guard illustrated in FIGURE 1;

FIGURE 3 is a top view of the guard illustrated in FIGURE 1;

FIGURE 4 is a perspective, exploded view of a preferred universal dolly for receiving and mounting a conventional gasoline-powered or electric line trimmer according to this invention;

FIGURE 5 is a side view, partially in section, of a typical bracket flange for mounting wheels, on the dolly illustrated in FIGURE 4;

FIGURE 6 is a top elevation of the universal dolly illustrated in FIGURE 4, assembled with left, right and rear wheels and a guard added to the horizontally-oriented dolly frame and an electric line trimmer mounted on the frame in mowing configuration;

FIGURE 7 is a top elevation of the universal dolly illustrated in FIGURE 1, with an electric line trimmer mounted on the dolly and the wheels oriented in outside rear wheel receptacles in trimming configuration;

FIGURE 8 is a side elevation of the universal dolly with the wheels mounted on the front wheel receptacles of the vertically-oriented dolly frame, to facilitate an edging function of the electric line trimmer along a sidewalk;

FIGURE 9 is a front elevation of the universal dolly illustrated in FIGURE 8, in the edging configuration;